Aberta Government

Siksika Bow River Hazard Study

We would like to provide an update on the status of the Siksika Bow River Hazard Study.

The multi-year study started in fall 2017 and technical work on all components is now complete.

We recognize there is tremendous interest in the study and new flood mapping products. We are currently seeking municipal and First Nation feedback on major study components as part of our study finalization process, including flood inundation maps that will support local emergency response in future flood seasons. We are exploring opportunities for future public engagement, and will provide an update when more information becomes available.

The Siksika Bow River Hazard Study is being completed under the provincial Flood Hazard Identification Program, the goals of which include enhancement of public safety and reduction of future flood damages through the identification of river and flood hazards. The provincial study was co-funded through the federal National Disaster Mitigation Program, with support from Indigenous Services Canada.

More information about the Alberta Flood Hazard Identification Program can be found at:

• <u>www.floodhazard.alberta.ca</u>

If you have any questions regarding this work, the project engagement specialist, Julia Frohlich, can be contacted at:

- Email: julia.frohlich@gov.ab.ca
- Telephone: 403 355-2494

Project Background and Study Progress

The Siksika Bow River Hazard Study assesses and identifies river-related hazards along 217 km of the Bow River downstream of the Highwood River confluence. The study area includes Siksika Nation, Foothills County, Rocky View County, Vulcan County, Wheatland County, and County of Newell, including Bow City.

The main study components outlined below include new hydraulic modelling and flood mapping, but all deliverables support local emergency response and land-use planning needs.

• Survey & Base Data Collection – Complete

Hydraulic models and flood maps require high-accuracy base data. Field surveys and LiDAR remote sensing were used to collect river and floodplain elevations, channel cross section data, bridge and culvert information, and dedicated flood control structure details.

• Hydrology Assessment – Complete

The hydrology assessment estimates flows for a wide range of possible floods along the Bow River, including the 2, 5, 10, 20, 35, 50, 75, 100, 200, 350, 500, 750 and 1000-year floods. The analysis includes data from the 2013 flood.

• Hydraulic River Modelling – Complete

A new hydraulic computer model of the river system was created using new survey data and modern tools. The model was calibrated using surveyed highwater marks from past floods to ensure that results for different floods are reasonable.

• Flood Inundation Mapping – Complete

Flood maps for thirteen different sized floods, based on the hydraulic model results and the hydrology assessment, have been produced. Flood inundation maps can be used for emergency response planning and to inform local infrastructure design. These maps identify areas of direct flooding and areas that could be flooded if local berms fail.

• Flood Hazard Mapping – Complete

Flood hazard mapping divides the 100-year floodplain into floodway and flood fringe zones, to identify where flooding is deepest and most destructive. These maps can be used to help guide long-term development planning.

• Flood Risk Assessment & Inventory – Complete

An inventory of structures at risk of flooding for all of the mapped flood scenarios can support future flood damage assessments.

Channel Stability Investigation – Complete

This investigation provides insight into general channel stability along the Bow River, and compares current and historic riverbank locations and channel cross sections as far back as 1949 using historic aerial photos.